



# ***SAW Components***

## ***Data Sheet***

### ***CQTSR403M55.03***

Customer's Approval Certificate	
Complies with Directive 2002/95/EC (RoHS)	
Please return this Page Via email as a certification of Your approval	
Checked & Approval by:	Date:


**Hangzhou Freq-control Electronics Technology Co.,Ltd.**

**TEL:0086-571-85803723**

**FAX:0086-571-85803724**

[sales@csimc-freqcontrol.com](mailto:sales@csimc-freqcontrol.com)

### 1. Package Dimension



Pin No.	Function
2	Input
4	Output
1,3	Case Ground

### 2. Marking

C6007	(1) Model code
A3	(2) Date code

A	3
Month code	Last figure of year

Month	1	2	3	4	5	6	7	8	9	10	11	12
Month code	A	B	C	D	E	F	G	H	I	J	K	L

### 3. Performance

#### 3.1 Application

One-port SAW Resonator for Wireless Remote Controller.

Center frequency: 403.55MHz

### 3.2 Maximum Rating

Rating		Value	Unit
Operating Temperature Range	$T_A$	-40 ~ +85	°C
Storage Temperature Range	$T_{stg}$	-45 ~ +85	°C
DC Voltage (between any Terminals)	$V_{DC}$	10	V
RF Power (in BW)	$P$	10	dBm
ESD Voltage (HB)	$V_{ESD}$	150	V

### 3.3 Electronic Characteristics

Item	Unit	Minimum	Typical	Maximum
Center Frequency ( $f_0$ )	MHz	403.475	403.55	403.625
Insertion Loss	dB	—	1.35	2.0
Quality Factor	—	—	—	—
Unloaded Q	—	—	15,000	—
50Ω Loaded Q	—	—	1,500	—
Temperature Stability	—	—	—	—
Turnover Temperature	°C	10	25	40
Frequency Temperature Coefficient	ppm/°C <sup>2</sup>	—	0.032	—
Frequency Aging	ppm/yr	—	<±10	—
DC Insulation Resistance	MΩ	1.0	—	—
RF Equivalent RLC Model	—	—	—	—
Motional Resistance $R_1$	Ω	—	15	24
Motional Inductance $L_1$	μH	—	89	—
Motional Capacitance $C_1$	fF	—	1.74	—
Shunt Static Capacitance $C_0$	pF	1.6	1.9	2.2

### 3.4 Test Circuit

