


1.Package Dimension Unit: mm

Pin No.	Function
2.	Input
5.	Output
4,8	Case Ground
Other	Ground

2.Electronic Characteristics

Electrostatic Sensitive Device (ESD)

Item	Units	Minimum	Typical	Maximum
Center Frequency (fo)	MHz	—	418.00	—
Insertion Loss (417.88~418.20MHz) ILmax	dB	—	3.5	5.0
3dB Bandwidth	KHz	800	850	—
Pass Band Ripple (relative to ILmin)				
417.85 ~ 418.23 MHz	dB	—	—	2.0
417.83 ~ 418.25 MHz	dB	—	—	3.0
417.78 ~ 418.30 MHz	dB	—	—	6.0
Relative Attenuation (relative to ILmin)				
10.0 ~ 400.0 MHz	dB	40	47	—
400.0 ~ 412.0 MHz	dB	35	40	—
412.0 ~ 417.0 MHz	dB	15	19	—
419.0 ~ 426.0 MHz	dB	12	17	—
426.0 ~ 435.0 MHz	dB	35	40	—
435.0 ~ 600.0 MHz	dB	38	42	—
600.0 ~ 1000.0 MHz	dB	45	50	—
External Impedance Match				
Series Inductance L	nH	—	39	—
Shunt Capacitance C	pF	—	6.8	—